



AGM Battery
 Part Number: PC680
 Nominal voltage: 12.85 Volts
 Description: Extreme conditions, high purity lead-tin alloy, dry cell technology, engine start & cycle

| Details | |
|-----------|------------------------------------------------------------------------------------------------|
| Case | Flame retardant cell containers, external metal jacket with decals. |
| Terminals | Removable SAE Automotive terminals with heli-coil thread and M6 stainless Allen key head bolt. |
| Colour | Cover: Odyssey Red; Case: Black; Sleeve (metal): Odyssey Red |

| Dimensions | |
|------------------------|--------|
| Length | 185 mm |
| Width | 79 mm |
| Height (inc terminals) | 187 mm |
| Weight | 7 Kg |

| Power Figures | |
|-----------------------------------------|-----------|
| PHCA 5 second (Pulse Hot Cranking Amps) | 680 amps |
| CCA (0°C) | 220 amps |
| HCA (26.6°C) | 370 amps |
| MCA (0°C) | 550 amps |
| Capacity (20 hour / C20) | 17 ah |
| Reserve Minutes | 24 mins |
| Internal Resistance | 7 mΩ |
| Short Circuit Current | 1800 amps |

| Life Cycle | |
|-----------------------|---------------|
| Design Life | 8-12 years |
| Cycles @ 80% D.O.D. | 500 cycles |
| Cycles @ 100% D.O.D. | 400 cycles |
| Operating Temperature | -40°C to 80°C |

Specifications subject to change without notice.