



ELF BIO NAUTIC

Prediluted biodegradable synthetic oil containing carefully selected additives for lubricating 2-stroke outboard motors.

APPLICATIONS

2-stroke outboards

Air-cooled 2-strokes

- Suitable for all 2-stroke gasoline outboard motors. The oil should be mixed with the fuel as indicated by the manufacturers.
- Can be used for air-cooled 2-stroke engines:
 - motorbikes,
 - chainsaws.

PERFORMANCE

API TC

TC-W3®

- API TC
- Officially approved under number: TC-W3®, recertified R-49000.
- Tested using the NMMA (National Marine Manufacturers Association) procedure.

CLIENT ADVANTAGES

Biodegradability

Good engine protection

Miscibility

- Biodegradable.
- Good stability in lead-free gasoline.
- Enhanced detergent, anticorrosion and antirust capability.
- Ash-free product.
- Very good anti-wear capability.
- Good miscibility with gasoline at low temperature.

CHARACTERISTICS

SG at 15°C	0.904	
Kinematic viscosity at 100°C	8.4	mm ² /s (cSt)
Pour point	-39	°C
PMCC flash point	204	°C
Biodegradability	82	%

(Typical values given as an illustration)

This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazard.

A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.

23.01.01 cancels and replaces that of 98.09

ELF BIO NAUTIC

